

# MALLARD WATCH

## TIME AND DATE SETTING INSTRUCTIONS

To assure maximum grater protection, Mallard Watches employ a screw-down crown. When you wish to reset the time or date on your watch, do the following:

1. Unscrew the crown until it's freed from the case tube.
2. To reset the date. pull the crown out one click.  
Then turn clockwise to correct date.
3. To reset the time, pull the crown out fully. Then turn the crown to correct time.  
Make sure the date changes at Midnight, not Noon.
4. To return the watch to its normal running status. press the crown in. Continue to press the crown inward and screw it into place. If you meet with resistance, unscrew it and start again until it screws on smoothly to avoid cross-threading which will damage the thread. Use only moderate turning effort to full seat the crown.

### **Setting Instructions For JB-W28 with Day/Date**

When you wish to reset the time or date on this watch, do the following:

1. Unscrew the crown until it's freed from the case tube.
2. To reset day or date:
  - a. Pull the crown out one click
  - b. Reset the date by turning the crown clockwise.
  - c. Reset the day by turning the crown counter-clockwise.
  - d. Push the crown inward to the neutral position.
3. To reset time:
  - a. Pull the crown all the way out.
  - b. Turn the crown to correct the time.

**IMPORTANT:** Be sure the day/date changes at Midnight, and not at Noon.

4. To return your watch to its normal running position, press the crown in. Continue to press the crown inward and screw it into place. If you meet with resistance, unscrew and start again until it screws on smoothly to avoid cross-threading which will damage the threads. Use only a moderate turning effort to fully seat the crown.